APPLICATION NOTES

Application Note 3018: Wire Length Limitations

APPLICATION NOTES

Table of Contents

Introduction	. 3
Max Wire Length via Outdoor Unit Communication	. 3
Max Total Wire Length	. 3
Max Wire Length from Outdoor Unit to Farthest Indoor Unit	. 4
Transmission Booster	. 5

Introduction

This Application Note provides an overview of allowable lengths of controls wiring

Max Wire Length via Outdoor Unit Communication

The maximum distance for communication via the outdoor unit central communication bus (TB7) is 1640 ft (500 m) is illustrated in Figure 1.




Figure 1: Maximum wire length for communication from outdoor unit

Max Total Wire Length

The maximum total wire length (sum of all M-NET wire) is 6560 ft (2 km).

Max Wire Length from Outdoor Unit to Farthest Indoor Unit

As shown in Figure 2, the maximum distance for communication from the outdoor unit (TB3) to the farthest indoor unit or ME remote controller is 656 ft (200 m).




Figure 2: Maximum wire length from outdoor unit to indoor unit

Transmission Booster

The transmission booster raises the signal voltage for applications that have a high number of devices powered by the M-NET. The outdoor unit TB3 power supply can power 32 units. Table 1 below details the M-NET power consumption of M-NET devices.

Table 1. M-Net p	oower c	consumption
------------------	---------	-------------

Device	Power (units)
Indoor Unit (P06-P54)	1
Indoor Unit (P72-P96)	7
BC Controller (CMB)	2
ME R/C (PAR-F27MEA)	0.5
SmartME R/C (PAR-U01MEDU-J)	0.5
DIDO Board (PAC-YG66DCA)	0.25
Al Board (PAC-YG63MCA)	0.25

When M-NET power consumption exceeds 32 units the transmission booster can be added to provide an additional 25 units of M-NET power. The transmission booster should be located in the middle of the TB3 communication bus to balance the power consumption as shown in Figure 3.

The transmission booster is supported by Diamond System Builder. We recommend using the Diamond System Builder to assist with applying the transmission booster.




Figure 3: Unit configuration using Transmission Booster

The transmission booster will not allow the M-NET to be extended beyond the maximum wire length limitation.